









Caratteristiche tecniche

				
Modello	HBA	HB2A	HBC	HB2C
Allacciamento elettrico	400V 3N 50Hz - Voltaggio speciale su richiesta			
Dimensioni				
Lunghezza x Profondità <i>mm</i>	1950 x 800	2550 x 800	2350 x 800	3250 x 800
Apertura <i>mm</i>	500x430(h)	500x430(h)	500x430(h)	500x430(h)
Altezza <i>mm</i>	1450	1450	1450	1450
Produzione ceste / ora				
1a velocità <i>ceste/h</i>	100	180	100	180
2a velocità <i>ceste/h</i>	150	270	150	270
Capot ingresso <i>mm</i>	400	400	400	400
Prelavaggio <i>mm</i>	-	600	-	900
Capacità vasca <i>l</i>	-	45	-	80
Potenza pompa <i>kW</i>	-	0,9	-	1,24
Riscaldamento vasca <i>kW</i>	-	-	-	9 (comm.)
Lavaggio <i>mm</i>	1150	1150	1150	1150
Capacità vasca <i>l</i>	80	80	80	80
Potenza pompa <i>kW</i>	1,24	1,24	1,24	1,24
Riscaldamento vasca <i>kW</i>	10	10	10	10
Risciacquo <i>mm</i>	-	-	400	400
Consumo acqua (1a vel.) <i>l/h</i>	250 (167 con HPRS)	350 (233 con HPRS)	167	233
Consumo acqua (2a vel.) <i>l/h</i>	250	350	250	350
Riscaldamento boiler <i>kW</i>	10	14	10	14
Asciugatura <i>mm</i>	600	600	600	600
Ventilatore <i>kW</i>	0,42	0,42	0,42	0,42
Batteria elettrica <i>kW</i>	6	6	6	6
Traino <i>kW</i>	0,18	0,18	0,18	0,18
Capot uscita <i>mm</i>	400	400	400	400
Carico vasche <i>l</i>	80	125	80	160
Potenza totale				
Standard (acqua a 55°C) <i>kW</i>	21,4	26,3	21,4	26,7
Con asciugatura <i>kW</i>	27,8	32,7	27,8	33,1
Con recuperatore <i>kW</i>	24	30,4	24	30,7

I dati indicati sono intesi per macchine alimentate ad acqua calda a 55°C.

Il fabbricante si riserva il diritto di variare i dati senza preavviso.

Technical specifications

Model				
	HBA	HB2A	HBC	HB2C
Electrical connection	400V 3N 50Hz - Special voltage on request			
Dimensions				
Length x Width	<i>mm</i> 1950 x 800	<i>mm</i> 2550 x 800	<i>mm</i> 2350 x 800	<i>mm</i> 3250 x 800
Clearance	<i>mm</i> 500x430(h)	<i>mm</i> 500x430(h)	<i>mm</i> 500x430(h)	<i>mm</i> 500x430(h)
Height	<i>mm</i> 1450	<i>mm</i> 1450	<i>mm</i> 1450	<i>mm</i> 1450
Baskets output / hour				
1st speed	<i>baskets/h</i> 100	<i>baskets/h</i> 180	<i>baskets/h</i> 100	<i>baskets/h</i> 180
2nd speed	<i>baskets/h</i> 150	<i>baskets/h</i> 270	<i>baskets/h</i> 150	<i>baskets/h</i> 270
Inlet hood	<i>mm</i> 400	<i>mm</i> 400	<i>mm</i> 400	<i>mm</i> 400
Prewash	<i>mm</i> -	<i>mm</i> 600	<i>mm</i> -	<i>mm</i> 900
Tank capacity	<i>l</i> -	<i>l</i> 45	<i>l</i> -	<i>l</i> 80
Pump power	<i>kW</i> -	<i>kW</i> 0,9	<i>kW</i> -	<i>kW</i> 1,24
Tank heating	<i>kW</i> -	<i>kW</i> -	<i>kW</i> -	<i>kW</i> 9 (comm.)
Wash	<i>mm</i> 1150	<i>mm</i> 1150	<i>mm</i> 1150	<i>mm</i> 1150
Tank capacity	<i>l</i> 80	<i>l</i> 80	<i>l</i> 80	<i>l</i> 80
Pump power	<i>kW</i> 1,24	<i>kW</i> 1,24	<i>kW</i> 1,24	<i>kW</i> 1,24
Tank heating	<i>kW</i> 10	<i>kW</i> 10	<i>kW</i> 10	<i>kW</i> 10
Rinse	<i>mm</i> -	<i>mm</i> -	<i>mm</i> 400	<i>mm</i> 400
Water consumption (1st speed)	<i>l/h</i> 250 (167 with HPRS)	<i>l/h</i> 350 (233 with HPRS)	<i>l/h</i> 167	<i>l/h</i> 233
Water consumption (2nd speed)	<i>l/h</i> 250	<i>l/h</i> 350	<i>l/h</i> 250	<i>l/h</i> 350
Boiler heating	<i>kW</i> 10	<i>kW</i> 14	<i>kW</i> 10	<i>kW</i> 14
Drying section	<i>mm</i> 600	<i>mm</i> 600	<i>mm</i> 600	<i>mm</i> 600
Fan	<i>kW</i> 0,42	<i>kW</i> 0,42	<i>kW</i> 0,42	<i>kW</i> 0,42
Heating element	<i>kW</i> 6	<i>kW</i> 6	<i>kW</i> 6	<i>kW</i> 6
Drive motor	<i>kW</i> 0,18	<i>kW</i> 0,18	<i>kW</i> 0,18	<i>kW</i> 0,18
Outlet hood	<i>mm</i> 400	<i>mm</i> 400	<i>mm</i> 400	<i>mm</i> 400
Tanks load	<i>l</i> 80	<i>l</i> 125	<i>l</i> 80	<i>l</i> 160
Total power				
Standard (water inlet 55°C)	<i>kW</i> 21,4	<i>kW</i> 26,3	<i>kW</i> 21,4	<i>kW</i> 26,7
With drying section (AS)	<i>kW</i> 27,8	<i>kW</i> 32,7	<i>kW</i> 27,8	<i>kW</i> 33,1
With heat recovery unit (RC)	<i>kW</i> 24	<i>kW</i> 30,4	<i>kW</i> 24	<i>kW</i> 30,7

Energy data refer to machines fed with hot water at 55°C. We recommend mains water supply at 55°C.

The company reserves the right to modify the data without notice.